




- Electrically or pneumatically actuated valves
- Valves with internal or external pilot air
- Manifold mounting for 2 ... 10 valves or individual mounting

Solenoid/pneumatic valves, midi pneumatics

Features

FESTO



Parameter	Variants	Possible combinations	Mounting
-  - Flow rate 200 ... 700 l/min -  - Width 18 mm -  - Voltage 24 V DC 110 or 230 V AC	- Electrically and pneumatically actuated valves 3/2, 5/2 and 5/3-way valves - Sub-base valves - Semi in-line valves	- Any number of valves can be added with series sub-bases 2 ... 10 manifold mounted valves with blanking plates for spare positions - Prefabricated plug socket with cable, LED and protective circuit - Cable and solenoid coil for assembly by user - Manual override	Semi in-line valves, threaded - Individual mounting Sub-base valves - Sub-base - Series sub-base Valves with in-line connection at top - PRS manifold

Solenoid/pneumatic valves, midi pneumatics

FESTO

Features

Mounting options

Individual sub-base

Connection at side

AS-ME-1/8

AS-VL-1/8



Connection underneath

AU-ME-1/8



Manifold mounting

Series sub-base

AW-ME-1/8



AW-VL-1/8



Intermediate plate

ZP-ME-1/8



End plate kit

EP-ME-1/8




Blanking plate for spare positions

PRMEB-5





In-line manifold

PRS-ME-1/8



Blanking plate for spare positions



PRSB-ME-1/8






Solenoid valves MEH/MEBH, midi pneumatics

FESTO

Overview – Solenoid valves

Function	Design	Type	Nominal flow rate [l/min]	Pneumatic connection	Operating voltage		Semi in-line valve	Sub-base valve
					[V DC]	[V AC]		
3/2-way valves		MEBH-3/2-...	700	5.0 mm	24	110, 230	–	■
			600	G $\frac{1}{8}$			■	–
		MOEBH-3/2-...	700	5.0 mm	24	110, 230	–	■
			600	G $\frac{1}{8}$			■	–
		MEH-3/2-...	700	5.0 mm	24	–	–	■
			600	G $\frac{1}{8}$			■	–
		MOEH-3/2-...	700	5.0 mm	24	–	–	■
			600	G $\frac{1}{8}$			■	–

Function	Design	Type	Nominal flow rate [l/min]	Pneumatic connection	Operating voltage		Semi in-line valve	Sub-base valve
					[V DC]	[V AC]		
5/2-way valves	Solenoid valve							
		MEBH-5/2-...	700	5.0 mm	24	110, 230	–	■
			600	G¼			■	–
		MEH-5/2-...	700	5.0 mm	24	–	–	■
			600	G¼			■	–
	Double solenoid valve							
		JMEBH-5/2-...	700	5.0 mm	24	110, 230	–	■
			650	G¼			■	–
		JMEH-5/2-...	700	5.0 mm	24	–	–	■
650			G¼	■			–	

Function	Design	Type	Nominal flow rate [l/min]	Pneumatic connection	Operating voltage		Semi in-line valve	Sub-base valve
					[V DC]	[V AC]		
5/3-way valves		MEBH-5/3...	500	5.0 mm	24	110, 230	–	■
			600	G $\frac{1}{8}$			■	–
			400	5.0 mm			–	■
			300	G $\frac{1}{8}$			■	–
			400	5.0 mm			–	■
			200	G $\frac{1}{8}$			■	–
		MEH-5/3...	500	5.0 mm	24	–	–	■
			600	G $\frac{1}{8}$			■	–
			400	5.0 mm			–	■
			300	G $\frac{1}{8}$			■	–
			400	5.0 mm			–	■
			200	G $\frac{1}{8}$			■	–

Solenoid valves MEH/MEBH, midi pneumatics

Overview – Solenoid valves

Type	Pilot air supply		Type of reset		Normal position		➔ Page/Internet
	internal	external	pneumatic spring	mechanical spring	closed	open	
Solenoid valve							
MEBH-3/2-...	■	–	–	■	■	–	9
MOEBH-3/2-...	■	–	–	■	–	■	
MEH-3/2-...	■	–	–	■	■	–	21
MOEH-3/2-...	■	–	–	■	–	■	

Type	Pilot air supply		Type of reset		Normal position		➔ Page/Internet
	internal	external	pneumatic spring	mechanical spring	closed	open	
Solenoid valve							
MEBH-5/2-...	■	■	■	■	–	–	9
MEH-5/2-...	■	■	■	■	–	–	21
Double solenoid valve							
JMEBH-5/2-...	■	■	–	–	–	–	9
JMEH-5/2-...	■	■	–	–	–	–	21


Type	Pilot air supply		Type of reset		Normal position			→ Page/Internet
	internal	external	pneumatic spring	mechanical spring	closed	exhausted	pressurised	
Solenoid valve								
MEBH-5/3...	■	■	–	■	■	–	–	9
	■	■	–	■	–	■	–	
	■	■	–	■	–	–	■	
MEH-5/3...	■	■	–	■	■	–	–	21
	■	■	–	■	–	■	–	
	■	■	–	■	–	–	■	

Pneumatic valves VL/J, midi pneumatics

FESTO

Overview – Pneumatic valves

Function	Design	Type	Nominal flow rate [l/min]	Pneumatic connection	Semi in-line valve	Sub-base valve
5/2-way valves	Pneumatic valve					
		VL-5/2-...	700	5.0 mm	–	■
			600	G $\frac{1}{8}$	■	–
	Double pilot valve					
		J-5/2-...	700	5.0 mm	–	■
			650	G $\frac{1}{8}$	■	–

Function	Design	Type	Nominal flow rate [l/min]	Pneumatic connection	Semi in-line valve	Sub-base valve
5/3-way valves	Pneumatic valve					
		VL-5/3...	600	5.0 mm	–	■
			500	G $\frac{1}{8}$	■	–
			350	5.0 mm	–	■
			350	G $\frac{1}{8}$	■	–
			300	5.0 mm	–	■
			300	G $\frac{1}{8}$	■	–

Pneumatic valves VL/J, midi pneumatics

Overview – Pneumatic valves

Type	Pilot air supply		Type of reset		→ Page/Internet
	internal	external	pneumatic spring	mechanical spring	
Pneumatic valve					
VL-5/2-...	■	–	–	■	34
Double pilot valve					
J-5/2-...	■	–	–	–	34

Type	Pilot air supply		Normal position			→ Page/Internet
	internal	external	closed	exhausted	pressurised	
Pneumatic valve						
VL-5/3...	■	–	■	–	–	34
	■	–	–	■	–	
	■	–	–	–	■	

Solenoid valves MEH/MEBH, midi pneumatics

FESTO

Type codes

MEBH – 5/2 – 1/8 – P – L – B – 110AC

Type	
MEBH	Single solenoid, with EB solenoid coil
MOEBH	Single solenoid, with EB solenoid coil, normally open
MEH	Single solenoid, with E solenoid coil
MOEH	Single solenoid, with E solenoid coil, normally open
JMEBH	Double solenoid, with EB solenoid coil
JMEH	Double solenoid, with E solenoid coil

Valve function	
3/2	3/2-way valve
5/2	5/2-way valve
5/3	5/3-way valve

Normal position	
G	Closed
E	Exhausted
B	Pressurised

Design, pneumatic connection/nominal size	
1/8	Semi in-line valve, thread G1/8
5.0	Sub-base valve, 5 mm

Mounting method	
P	On manifold PRS-ME

Type of reset	
	Mechanical spring
L	Pneumatic spring

Pilot air supply	
	Internal
S	External

Generation	
B	B series

Operating voltage	
	24 V DC
110AC	110 V AC
230AC	230 V AC


Solenoid valves MEBH, midi pneumatics

FESTO

Technical data

-  - Flow rate
200 ... 700 l/min

-  - Voltage
24 V DC
110/230 V AC



General technical data							
Type		MEBH-3/2-...	MEBH-5/2-...	JMEBH-5/2-...	MEBH-5/3...		
		MOEBH-3/2-...					
Design		Piston spool					
Type of mounting	...-1/8	2 through-holes					
	...-5.0	On sub-base with two M3 screws					
	...-1/8-P	On manifold with two M3 screws					
Pneumatic connection	...-1/8	G1/8					
	...-5.0	Sub-base					
	...-1/8-P	G1/8					
Nominal size	[mm]	5					
Standard nominal flow rate	[l/min]				G	E	B
1 > 2, 1 > 4	...-1/8	600/500	600	650	600	300	200
	...-5.0	700/600	700	700	500	400	400
	...-1/8-P	600/500	600	650	650	300	200
Materials		Housing: Aluminium Seals: Nitrile rubber					
Weight	[g]	...-1/8	105	105	142	153	
		...-5.0	105	105	146	150	
		...-1/8-P	105	105	142	153	

Operating and environmental conditions						
Type			MEBH-3/2-... MOEBH-3/2-...	MEBH-5/2-...	JMEBH-5/2-...	MEBH-5/3...
Operating medium			Compressed air in accordance with ISO 8573-1:2010 [7:4:4] ¹⁾			
Note on operating/pilot medium			Operation with lubricated medium possible (in which case lubricated operation will always be required)			
Operating pressure range	Internal pilot air supply	[bar]	2 ... 8	2.5 ... 8	1.5 ... 8	3 ... 8
	External pilot air supply	[bar]	–	–0.9 ... +10		
Pilot pressure range		[bar]	–	2.5 ... 8	1.5 ... 8	3 ... 8
Ambient temperature		[°C]	–5 ... +50			
Temperature of medium		[°C]	–5 ... +50			
Note on materials			RoHS-compliant			

1) Only oils of viscosity class 32 may be used for lubricated operation.

Solenoid valves MEBH, midi pneumatics



Technical data

Valve response times [ms]							
Type	MEBH-3/2-... MOEBH-3/2-...		MEBH-5/2-...		JMEBH-5/2-...	MEBH-5/3...	
Type of reset	mechanical	pneumatic	mechanical	pneumatic	–	mechanical	pneumatic
On	10	–	10	15	–	12	–
Off	28	–	28	18	–	25	–
Changeover	–	–	–	–	10	–	–

Electrical data			
EB solenoid coil			
Electrical connection		Plug, square design to EN 175301-803, type C	
Operating voltage	D.C. voltage	[V DC]	24
	AC voltage	[V AC]	110/230 (50 ... 60 Hz)
Coil characteristics	D.C. voltage	[W]	1.5
	AC voltage	[VA]	2.4
Protection class to EN 60 529		IP65 (in combination with plug socket)	

Solenoid valves MEBH, midi pneumatics


Technical data – 3/2-way valves

FESTO

Dimensions


Download CAD data → www.festo.com

Semi in-line valve with thread G1/8



- 1 Solenoid coil can be rotated 180°¹⁾
 - 2 Manual override
 - 3 Suitable for plug sockets to EN 175 301-803, form C: MSSD-EB or KMEB-...
 - 4 Manual override tool (accessory) AHB-ME-1/8
- 1) The seal must not be turned!

Semi in-line valve for manifold PRS-ME



- 1 Solenoid coil can be rotated 180°¹⁾
 - 2 Manual override
 - 3 Suitable for plug sockets to EN 175 301-803, form C: MSSD-EB or KMEB-...
 - 4 Manual override tool (accessory) AHB-ME-1/8
- 1) The seal must not be turned!

Solenoid valves MEBH, midi pneumatics


Technical data – 3/2-way valves

FESTO

Dimensions

Download CAD data → www.festo.com



Sub-base valve



- 1 Solenoid coil can be rotated 180°¹⁾
- 2 Manual override
- 3 Suitable for plug sockets to EN 175 301-803, form C: MSSD-EB or KMEB-...
- 4 Manual override tool (accessory)
AHB-ME-1/8

1) The seal must not be turned!

Ordering data

Circuit symbol	Description	Voltage	Part No.	Type
Normally closed				
	Semi in-line valve with thread G1/8	24 V DC	172998	MEBH-3/2-1/8-B
		110 V AC	173042	MEBH-3/2-1/8-B-110AC
		230 V AC	173084	MEBH-3/2-1/8-B-230AC
	Semi in-line valve for manifold PRS-ME	24 V DC	173000	MEBH-3/2-1/8-P-B
		110 V AC	173056	MEBH-3/2-1/8-P-B-110AC
		230 V AC	173098	MEBH-3/2-1/8-P-B-230AC
	Sub-base valve	24 V DC	172999	MEBH-3/2-5,0-B
		110 V AC	173070	MEBH-3/2-5,0-B-110AC
		230 V AC	173112	MEBH-3/2-5,0-B-230AC
Normally open				
	Semi in-line valve with thread G1/8	24 V DC	173001	MOEBH-3/2-1/8-B
		110 V AC	173053	MOEBH-3/2-1/8-B-110AC
		230 V AC	173095	MOEBH-3/2-1/8-B-230AC
	Semi in-line valve for manifold PRS-ME	24 V DC	173003	MOEBH-3/2-1/8-P-B
		110 V AC	173067	MOEBH-3/2-1/8-P-B-110AC
	Sub-base valve	24 V DC	173002	MOEBH-3/2-5,0-B

Solenoid valves MEBH, midi pneumatics


Technical data – 5/2-way valves

FESTO

Dimensions

Download CAD data → www.festo.com


Semi in-line valve with thread G1/8



- 1 Solenoid coil can be rotated 180°¹⁾
- 2 Manual override
- 3 Suitable for plug sockets to EN 175301-803, form C: MSSD-EB or KMEB-...
- 4 Manual override tool (accessory) AHB-ME-1/8
- 5 Port for external pilot air on S types

1) The seal must not be turned!

Semi in-line valve for manifold PRS-ME



- 1 Solenoid coil can be rotated 180°¹⁾
- 2 Manual override
- 3 Suitable for plug sockets to EN 175301-803, form C: MSSD-EB or KMEB-...
- 4 Manual override tool (accessory) AHB-ME-1/8
- 5 Port for external pilot air on S types

1) The seal must not be turned!

Solenoid valves MEBH, midi pneumatics


Technical data – 5/2-way valves

FESTO

Dimensions

Download CAD data → www.festo.com

Sub-base valve







- 1 Solenoid coil can be rotated 180°¹⁾
- 2 Manual override
- 3 Suitable for plug sockets to EN 175 301-803, form C: MSSD-EB or KMEB-...
- 4 Manual override tool (accessory) AHB-ME-1/8
- 5 Port for external pilot air on S types

1) The seal must not be turned!

Solenoid valves MEBH, midi pneumatics

FESTO

Technical data – 5/2-way valves

Ordering data				
Circuit symbol	Description	Voltage	Part No.	Type
Mechanical spring return, internal pilot air supply				
	Semi in-line valve with thread G1/8	24 V DC	173004	MEBH-5/2-1/8-B
		110 V AC	173043	MEBH-5/2-1/8-B-110AC
		230 V AC	173085	MEBH-5/2-1/8-B-230AC
	Semi in-line valve for manifold PRS-ME	24 V DC	173006	MEBH-5/2-1/8-P-B
		110 V AC	173057	MEBH-5/2-1/8-P-B-110AC
		230 V AC	173099	MEBH-5/2-1/8-P-B-230AC
	Sub-base valve	24 V DC	173005	MEBH-5/2-5,0-B
		110 V AC	173071	MEBH-5/2-5,0-B-110AC
		230 V AC	173113	MEBH-5/2-5,0-B-230AC
Mechanical spring return, external pilot air supply				
	Semi in-line valve with thread G1/8	24 V DC	173007	MEBH-5/2-1/8-S-B
		110 V AC	173046	MEBH-5/2-1/8-S-B-110AC
		230 V AC	173088	MEBH-5/2-1/8-S-B-230AC
	Semi in-line valve for manifold PRS-ME	24 V DC	173009	MEBH-5/2-1/8-P-S-B
		110 V AC	173060	MEBH-5/2-1/8-P-S-B-110AC
		230 V AC	173102	MEBH-5/2-1/8-P-S-B-230AC
	Sub-base valve	24 V DC	173008	MEBH-5/2-5,0-S-B
		110 V AC	173074	MEBH-5/2-5,0-S-B-110AC
		230 V AC	173116	MEBH-5/2-5,0-S-B-230AC
Pneumatic spring return, internal pilot air supply				
	Semi in-line valve with thread G1/8	24 V DC	173010	MEBH-5/2-1/8-L-B
		110 V AC	173044	MEBH-5/2-1/8-L-B-110AC
		230 V AC	173086	MEBH-5/2-1/8-L-B-230AC
	Semi in-line valve for manifold PRS-ME	24 V DC	173012	MEBH-5/2-1/8-P-L-B
		110 V AC	173058	MEBH-5/2-1/8-P-L-B-110AC
		230 V AC	173100	MEBH-5/2-1/8-P-L-B-230AC
	Sub-base valve	24 V DC	173011	MEBH-5/2-5,0-L-B
		110 V AC	173072	MEBH-5/2-5,0-L-B-110AC
		230 V AC	173114	MEBH-5/2-5,0-L-B-230AC
Pneumatic spring return, external pilot air supply				
	Semi in-line valve with thread G1/8	24 V DC	173013	MEBH-5/2-1/8-L-S-B
	Semi in-line valve for manifold PRS-ME	24 V DC	173015	MEBH-5/2-1/8-P-L-S-B
		110 V AC	173059	MEBH-5/2-1/8-P-L-S-B-110AC
	Sub-base valve	24 V DC	173014	MEBH-5/2-5,0-L-S-B
		110 V AC	173073	MEBH-5/2-5,0-L-S-B-110AC

Solenoid valves MEBH, midi pneumatics


Technical data – 5/2-way valves, double solenoid

FESTO

Dimensions

Download CAD data → www.festo.com


Semi in-line valve with thread G $\frac{1}{8}$



- 1 Solenoid coil can be rotated 180°¹⁾
- 2 Manual override
- 3 Suitable for plug sockets to EN 175 301-803, form C: MSSD-EB or KMEB-...
- 4 Manual override tool (accessory) AHB-ME-1/8
- 5 Port for external pilot air on S types

1) The seal must not be turned!

Semi in-line valve for manifold PRS-ME



- 1 Solenoid coil can be rotated 180°¹⁾
- 2 Manual override
- 3 Suitable for plug sockets to EN 175 301-803, form C: MSSD-EB or KMEB-...
- 4 Manual override tool (accessory) AHB-ME-1/8
- 5 Port for external pilot air on S types

1) The seal must not be turned!

Solenoid valves MEBH, midi pneumatics


Technical data – 5/2-way valves, double solenoid

FESTO

Dimensions

Download CAD data → www.festo.com



Sub-base valve



- 1 Solenoid coil can be rotated 180°¹⁾
- 2 Manual override
- 3 Suitable for plug sockets to EN 175 301-803, form C: MSSD-EB or KMEB-...
- 4 Manual override tool (accessory) AHB-ME-1/8
- 5 Port for external pilot air on S types

1) The seal must not be turned!

Ordering data

Circuit symbol	Description	Voltage	Part No.	Type
Internal pilot air supply				
	Semi in-line valve with thread G1/8	24 V DC	173034	JMEBH-5/2-1/8-B
		110 V AC	173040	JMEBH-5/2-1/8-B-110AC
		230 V AC	173082	JMEBH-5/2-1/8-B-230AC
	Semi in-line valve for manifold PRS-ME	24 V DC	173036	JMEBH-5/2-1/8-P-B
		110 V AC	173054	JMEBH-5/2-1/8-P-B-110AC
		230 V AC	173096	JMEBH-5/2-1/8-P-B-230AC
	Sub-base valve	24 V DC	173035	JMEBH-5/2-5,0-B
		110 V AC	173068	JMEBH-5/2-5,0-B-110AC
		230 V AC	173110	JMEBH-5/2-5,0-B-230AC
External pilot air supply				
	Semi in-line valve with thread G1/8	24 V DC	173037	JMEBH-5/2-1/8-S-B
		230 V AC	173083	JMEBH-5/2-1/8-S-B-230AC
	Semi in-line valve for manifold PRS-ME	110 V AC	173055	JMEBH-5/2-1/8-P-S-B-110AC
		230 V AC	173097	JMEBH-5/2-1/8-P-S-B-230AC
	Sub-base valve	24 V DC	173038	JMEBH-5/2-5,0-S-B
		230 V AC	173111	JMEBH-5/2-5,0-S-B-230AC

Solenoid valves MEBH, midi pneumatics


Technical data – 5/3-way valves

FESTO


Dimensions

Download CAD data → www.festo.com

Semi in-line valve with thread G $\frac{1}{8}$



Semi in-line valve for manifold PRS-ME



Solenoid valves MEBH, midi pneumatics


Technical data – 5/3-way valves

FESTO

Dimensions

Download CAD data → www.festo.com

Sub-base valve



- 1 Solenoid coil can be rotated 180°¹⁾
- 2 Manual override
- 3 Suitable for plug sockets to EN 175 301-803, form C: MSSD-EB or KMEB-...
- 4 Manual override tool (accessory) AHB-ME-1/8
- 5 Port for external pilot air on S types

1) The seal must not be turned!





Ordering data

Circuit symbol	Description	Voltage	Part No.	Type
Normally closed, internal pilot air supply				
	Semi in-line valve with thread G1/8	24 V DC	173016	MEBH-5/3G-1/8-B
		230 V AC	173093	MEBH-5/3G-1/8-B-230AC
	Semi in-line valve for manifold PRS-ME	24 V DC	173018	MEBH-5/3G-1/8-P-B
		110 V AC	173065	MEBH-5/3G-1/8-P-B-110AC
		230 V AC	173107	MEBH-5/3G-1/8-P-B-230AC
	Sub-base valve	24 V DC	173017	MEBH-5/3G-5,0-B
		110 V AC	173079	MEBH-5/3G-5,0-B-110AC
		230 V AC	173121	MEBH-5/3G-5,0-B-230AC
Normally closed, external pilot air supply				
	Semi in-line valve with thread G1/8	24 V DC	173019	MEBH-5/3G-1/8-S-B
	Semi in-line valve for manifold PRS-ME	24 V DC	173021	MEBH-5/3G-1/8-P-S-B
	Sub-base valve	24 V DC	173020	MEBH-5/3G-5,0-S-B
		230 V AC	173122	MEBH-5/3G-5,0-S-B-230AC

Solenoid valves MEBH, midi pneumatics

FESTO

Technical data – 5/3-way valves

Ordering data				
Circuit symbol	Description	Voltage	Part No.	Type
Normally exhausted, internal pilot air supply				
	Semi in-line valve with thread G1/8	24 V DC	173022	MEBH-5/3E-1/8-B
		230 V AC	173091	MEBH-5/3E-1/8-B-230AC
	Semi in-line valve for manifold PRS-ME	24 V DC	173024	MEBH-5/3E-1/8-P-B
		110 V AC	173063	MEBH-5/3E-1/8-P-B-110AC
	Sub-base valve	24 V DC	173023	MEBH-5/3E-5,0-B
		110 V AC	173077	MEBH-5/3E-5,0-B-110AC
	230 V AC	173119	MEBH-5/3E-5,0-B-230AC	
Normally exhausted, external pilot air supply				
	Semi in-line valve for manifold PRS-ME	24 V DC	173027	MEBH-5/3E-1/8-P-S-B
	Sub-base valve	24 V DC	173026	MEBH-5/3E-5,0-S-B
		230 V AC	173120	MEBH-5/3E-5,0-S-B-230AC
Normally pressurised, internal pilot air supply				
	Semi in-line valve with thread G1/8	24 V DC	173028	MEBH-5/3B-1/8-B
		230 V AC	173089	MEBH-5/3B-1/8-B-230AC
	Semi in-line valve for manifold PRS-ME	24 V DC	173030	MEBH-5/3B-1/8-P-B
		230 V AC	173103	MEBH-5/3B-1/8-P-B-230AC
	Sub-base valve	24 V DC	173029	MEBH-5/3B-5,0-B
Normally pressurised, external pilot air supply				
	Semi in-line valve with thread G1/8	24 V DC	173031	MEBH-5/3B-1/8-S-B
	Sub-base valve	24 V DC	173032	MEBH-5/3B-5,0-S-B


Solenoid valves MEH, midi pneumatics

FESTO

Technical data

-  - Flow rate
200 ... 700 l/min

-  - Voltage
24 V DC



General technical data							
Type		MEH-3/2-... MOEH-3/2-...	MEH-5/2-...	JMEH-5/2-...	MEH-5/3...		
Design		Piston spool					
Type of mounting	...-1/8	2 through-holes					
	...-5.0	On sub-base with two M3 screws					
	...-1/8-P	On manifold with two M3 screws					
Pneumatic connection	...-1/8	G1/8					
	...-5.0	Sub-base					
	...-1/8-P	G1/8					
Nominal size	[mm]	5					
Standard nominal flow rate	[l/min]				G	E	B
1 > 2, 1 > 4	...-1/8	600/500	600	650	600	300	200
	...-5.0	700/600	700	700	500	400	400
	...-1/8-P	600/500	600	650	650	300	200
Materials		Housing: Aluminium Seals: Nitrile rubber					
Weight	[g]	...-1/8	105	105	142	153	
	...-5.0	105	105	146	150		
	...-1/8-P	105	105	142	153		

Operating and environmental conditions						
Type			MEH-3/2-... MOEH-3/2-...	MEH-5/2-...	JMEH-5/2-...	MEH-5/3...
Operating medium			Compressed air in accordance with ISO 8573-1:2010 [7:4:4] ¹⁾			
Note on operating/pilot medium			Operation with lubricated medium possible (in which case lubricated operation will always be required)			
Operating pressure range	Internal pilot air supply	[bar]	2 ... 8	2.5 ... 8	1.5 ... 8	3 ... 8
	External pilot air supply	[bar]	–	–0.9 ... +10		
Pilot pressure range		[bar]	–	2.5 ... 8	1.5 ... 8	3 ... 8
Ambient temperature		[°C]	–5 ... +50			
Temperature of medium		[°C]	–5 ... +50			
Note on materials			RoHS-compliant			

1) Only oils of viscosity class 32 may be used for lubricated operation.

Solenoid valves MEH, midi pneumatics




Technical data

Valve response times [ms]							
Type	MEH-3/2-... MOEH-3/2-...		MEH-5/2-...		JMEH-5/2-...	MEH-5/3...	
Type of reset	mechanical	pneumatic	mechanical	pneumatic	–	mechanical	pneumatic
On	10	–	10	15	–	12	–
Off	28	–	28	18	–	25	–
Changeover	–	–	–	–	10	–	–

Electrical data	
E solenoid coil	
Electrical connection	Plug, square, connection pattern type C, to industry standard 9.4 mm
Operating voltage	[V DC] 24
Coil characteristics	[W] 1.5
Protection class to EN 60 529	IP65 (in combination with plug socket)


Technical data – 3/2-way valves

Semi in-line valve with thread G1/8



1) The seal must not be turned!

Semi in-line valve for manifold PRS-ME



1) The seal must not be turned!

Solenoid valves MEH, midi pneumatics


Technical data – 3/2-way valves

FESTO

Dimensions



Download CAD data → www.festo.com

Sub-base valve



- 1) Solenoid coil can be rotated 180°¹⁾
 - 2) Manual override
 - 3) Suitable for terminal sockets to DIN 46 247 or plug sockets MSSD-E type KME type
 - 4) Manual override tool (accessory) AHB-ME-1/8
- 1) The seal must not be turned!

Ordering data

Circuit symbol	Description	Voltage	Part No.	Type
Normally closed				
	Semi in-line valve with thread G1/8	24 V DC	173124	MEH-3/2-1/8-B
	Semi in-line valve for manifold PRS-ME		173126	MEH-3/2-1/8-P-B
	Sub-base valve		173125	MEH-3/2-5,0-B
Normally open				
	Semi in-line valve with thread G1/8	24 V DC	173428	MOEH-3/2-1/8-B
	Semi in-line valve for manifold PRS-ME		173430	MOEH-3/2-1/8-P-B
	Sub-base valve		173429	MOEH-3/2-5,0-B

Solenoid valves MEH, midi pneumatics


Technical data – 5/2-way valves

FESTO

Dimensions

Download CAD data → www.festo.com


Semi in-line valve with thread G $\frac{1}{8}$



- 1) Solenoid coil can be rotated 180°¹⁾
- 2) Manual override
- 3) Suitable for terminal sockets to DIN 46247 or plug sockets MSSD-E type KME type
- 4) Manual override tool (accessory) AHB-ME- $\frac{1}{8}$
- 5) Port for external pilot air on S types

1) The seal must not be turned!

Semi in-line valve for manifold PRS-ME



- 1) Solenoid coil can be rotated 180°¹⁾
- 2) Manual override
- 3) Suitable for terminal sockets to DIN 46247 or plug sockets MSSD-E type KME type
- 4) Manual override tool (accessory) AHB-ME- $\frac{1}{8}$
- 5) Port for external pilot air on S types

1) The seal must not be turned!

Solenoid valves MEH, midi pneumatics


Technical data – 5/2-way valves

FESTO

Dimensions

Download CAD data → www.festo.com

Sub-base valve







- 1 Solenoid coil can be rotated 180°¹⁾
- 2 Manual override
- 3 Suitable for terminal sockets to DIN 46247 or plug sockets MSSD-E type KME type
- 4 Manual override tool (accessory) AHB-ME-1/8
- 5 Port for external pilot air on S types

1) The seal must not be turned!

Solenoid valves MEH, midi pneumatics

Technical data – 5/2-way valves

Ordering data				
Circuit symbol	Description	Voltage	Part No.	Type
Mechanical spring return, internal pilot air supply				
	Semi in-line valve with thread G1/8	24 V DC	173127	MEH-5/2-1/8-B
	Semi in-line valve for manifold PRS-ME		173129	MEH-5/2-1/8-P-B
	Sub-base valve		173128	MEH-5/2-5,0-B
Mechanical spring return, external pilot air supply				
	Semi in-line valve with thread G1/8	24 V DC	173130	MEH-5/2-1/8-S-B
	Semi in-line valve for manifold PRS-ME		173132	MEH-5/2-1/8-P-S-B
	Sub-base valve		173131	MEH-5/2-5,0-S-B
Pneumatic spring return, internal pilot air supply				
	Semi in-line valve with thread G1/8	24 V DC	173133	MEH-5/2-1/8-L-B
	Semi in-line valve for manifold PRS-ME		173135	MEH-5/2-1/8-P-L-B
	Sub-base valve		173134	MEH-5/2-5,0-L-B
Pneumatic spring return, external pilot air supply				
	Semi in-line valve with thread G1/8	24 V DC	173136	MEH-5/2-1/8-L-S-B
	Semi in-line valve for manifold PRS-ME		173138	MEH-5/2-1/8-P-L-S-B
	Sub-base valve		173137	MEH-5/2-5,0-L-S-B

Solenoid valves MEH, midi pneumatics


Technical data – 5/2-way valves, double solenoid

FESTO

Dimensions

Download CAD data → www.festo.com


Semi in-line valve with thread G $\frac{1}{8}$



- 1 Solenoid coil can be rotated 180°¹⁾
- 2 Manual override
- 3 Suitable for terminal sockets to DIN 46 247 or plug sockets MSSD-E type KME type
- 4 Manual override tool (accessory) AHB-ME- $\frac{1}{8}$
- 5 Port for external pilot air on S types

1) The seal must not be turned!

Semi in-line valve for manifold PRS-ME



- 1 Solenoid coil can be rotated 180°¹⁾
- 2 Manual override
- 3 Suitable for terminal sockets to DIN 46 247 or plug sockets MSSD-E type KME type
- 4 Manual override tool (accessory) AHB-ME- $\frac{1}{8}$
- 5 Port for external pilot air on S types

1) The seal must not be turned!

Solenoid valves MEH, midi pneumatics


Technical data – 5/2-way valves, double solenoid

FESTO

Dimensions

Download CAD data → www.festo.com

Sub-base valve



- 1 Solenoid coil can be rotated 180°¹⁾
 - 2 Manual override
 - 3 Suitable for terminal sockets to DIN 46 247 or plug sockets MSSD-E type KME type
 - 4 Manual override tool (accessory) AHB-ME-1/8
 - 5 Port for external pilot air on S types
- 1) The seal must not be turned!

Ordering data

Circuit symbol	Description	Voltage	Part No.	Type
5/2-way valves				
Internal pilot air supply				
	Semi in-line valve with thread G1/8	24 V DC	173431	JMEH-5/2-1/8-B
	Semi in-line valve for manifold PRS-ME		173433	JMEH-5/2-1/8-P-B
	Sub-base valve		173432	JMEH-5/2-5,0-B
External pilot air supply				
	Semi in-line valve with thread G1/8	24 V DC	173434	JMEH-5/2-1/8-S-B
	Semi in-line valve for manifold PRS-ME		173436	JMEH-5/2-1/8-P-S-B
	Sub-base valve		173435	JMEH-5/2-5,0-S-B

Solenoid valves MEH, midi pneumatics


Technical data – 5/3-way valves

FESTO

Dimensions

Semi in-line valve with thread G $\frac{1}{8}$


Download CAD data → www.festo.com



- 1 Solenoid coil can be rotated 180°¹⁾
- 2 Manual override
- 3 Suitable for terminal sockets to DIN 46 247 or plug sockets MSSD-E type KME type
- 4 Manual override tool (accessory) AHB-ME- $\frac{1}{8}$
- 5 Port for external pilot air on S types

1) The seal must not be turned!

Semi in-line valve for manifold PRS-ME



- 1 Solenoid coil can be rotated 180°¹⁾
- 2 Manual override
- 3 Suitable for terminal sockets to DIN 46 247 or plug sockets MSSD-E type KME type
- 4 Manual override tool (accessory) AHB-ME- $\frac{1}{8}$
- 5 Port for external pilot air on S types

1) The seal must not be turned!

Solenoid valves MEH, midi pneumatics


Technical data – 5/3-way valves

FESTO

Dimensions

Download CAD data → www.festo.com

Sub-base valve









- 1 Solenoid coil can be rotated 180°¹⁾
 - 2 Manual override
 - 3 Suitable for terminal sockets to DIN 46 247 or plug sockets MSSD-E type KME type
 - 4 Manual override tool (accessory) AHB-ME-1/8
 - 5 Port for external pilot air on S types
- 1) The seal must not be turned!

Solenoid valves MEH, midi pneumatics

FESTO

Technical data – 5/3-way valves

Ordering data				
Circuit symbol	Description	Voltage	Part No.	Type
Normally closed, internal pilot air supply				
	Semi in-line valve with thread G1/8	24 V DC	173139	MEH-5/3G-1/8-B
	Semi in-line valve for manifold PRS-ME		173141	MEH-5/3G-1/8-P-B
	Sub-base valve		173140	MEH-5/3G-5,0-B
Normally closed, external pilot air supply				
	Semi in-line valve with thread G1/8	24 V DC	173142	MEH-5/3G-1/8-S-B
	Semi in-line valve for manifold PRS-ME		173144	MEH-5/3G-1/8-P-S-B
	Sub-base valve		173143	MEH-5/3G-5,0-S-B
Normally exhausted, internal pilot air supply				
	Semi in-line valve with thread G1/8	24 V DC	173145	MEH-5/3E-1/8-B
	Semi in-line valve for manifold PRS-ME		173147	MEH-5/3E-1/8-P-B
	Sub-base valve		173146	MEH-5/3E-5,0-B
Normally exhausted, external pilot air supply				
	Semi in-line valve with thread G1/8	24 V DC	173148	MEH-5/3E-1/8-S-B
	Semi in-line valve for manifold PRS-ME		173150	MEH-5/3E-1/8-P-S-B
	Sub-base valve		173149	MEH-5/3E-5,0-S-B
Normally pressurised, internal pilot air supply				
	Semi in-line valve with thread G1/8	24 V DC	173151	MEH-5/3B-1/8-B
	Semi in-line valve for manifold PRS-ME		173153	MEH-5/3B-1/8-P-B
	Sub-base valve		173152	MEH-5/3B-5,0-B
Normally pressurised, external pilot air supply				
	Semi in-line valve with thread G1/8	24 V DC	173154	MEH-5/3B-1/8-S-B
	Semi in-line valve for manifold PRS-ME		173156	MEH-5/3B-1/8-P-S-B

Pneumatic valves VL/J, midi pneumatics

Type codes

FESTO


		VL	–	5/3	B	–	1/8	–	P	–	B
Type											
VL	Single solenoid										
J	Double solenoid										
Valve function											
5/2	5/2-way valve										
5/3	5/3-way valve										
Normal position											
G	Closed										
E	Exhausted										
B	Pressurised										
Design, pneumatic connection/nominal size											
1/8	Semi in-line valve, thread G1/8										
5.0	Sub-base valve, 5 mm										
Mounting method											
P	On manifold PRS-ME										
Generation											
B	B series										

Pneumatic valves VL/J, midi pneumatics

FESTO

Technical data

Flow rate
300 ... 700 l/min



General technical data						
Type		VL-5/2-...	J-5/2-...	VL-5/3...		
Design		Piston spool, directly actuated				
Type of mounting	...-1/8	2 through-holes				
	...-5.0	On sub-base with two M3 screws				
	...-1/8-P	On manifold with two M3 screws				
Pneumatic connection	Working lines	...-1/8	G1/8			
		...-5.0	On sub-base			
		...-1/8-P	G1/8			
	Pilot line	M5				
Nominal size	[mm]	5				
Standard nominal flow rate	[l/min]			G	E	B
1 → 2, 1 → 4	...-1/8	600	650	500	350	300
	...-5.0	700	700	600	350	300
	...-1/8-P	600	650	500	350	300
Pilot air supply		External				
Direction of flow		Reversible				
Materials		Housing: Aluminium Seals: Nitrile rubber				
Weight	[g]	...-1/8	75	75	95	
		...-5.0	65	65	85	
		...-1/8-P	60	60	80	

Operating and environmental conditions			
Type		VL-5/2-...	J-5/2-... VL-5/3...
Operating medium		Compressed air in accordance with ISO 8573-1:2010 [7:4:4] ¹⁾	
Note on operating/pilot medium		Operation with lubricated medium possible (in which case lubricated operation will always be required)	
Operating pressure range	[bar]	-0.9 ... +10	
Pilot pressure range	[bar]	2.5 ... 8	1.5 ... 8 3 ... 8
Ambient temperature	[°C]	-5 ... +50	
Temperature of medium	[°C]	-5 ... +50	
Note on materials		RoHS-compliant	

1) Only oils of viscosity class 32 may be used for lubricated operation.

Valve response times [ms]			
Type		VL-5/2-...	J-5/2-... VL-5/3...
On		6	6
Off		24	22
Changeover		-	5 -

Pneumatic valves VL/J, midi pneumatics


FESTO

Technical data – 5/2-way valves


Dimensions

Download CAD data → www.festo.com


Semi in-line valve with thread G $\frac{1}{8}$



Semi in-line valve for manifold PRS-ME



Sub-base valve



Ordering data



Circuit symbol	Description	Part No.	Type
	Semi in-line valve with thread G $\frac{1}{8}$	173168	VL-5/2- $\frac{1}{8}$ -B
	Sub-base valve	173169	VL-5/2-5,0-B
	Semi in-line valve for manifold PRS-ME	173170	VL-5/2- $\frac{1}{8}$ -P-B

Technical data – 5/2-way valves, double pilot

Dimensions

Semi in-line valve with thread G1/8

Semi in-line valve for manifold PRS-ME

[illegible]

Circuit symbol

Circuit symbol	Description	Part No.	Type
	Semi in-line valve with thread G $\frac{1}{8}$	173171	J-5/2- $\frac{1}{8}$ -B
	Sub-base valve	173172	J-5/2-5,0-B
	Semi in-line valve for manifold PRS-ME	173173	J-5/2- $\frac{1}{8}$ -P-B

Pneumatic valves VL/J, midi pneumatics

FESTO



Technical data – 5/3-way valves

Dimensions


Download CAD data → www.festo.com

Semi in-line valve with thread G1/8

Semi in-line valve for manifold PRS-ME






Sub-base valve



Pneumatic valves VL/J, midi pneumatics

FESTO

Technical data – 5/3-way valves

Ordering data			
Circuit symbol	Description	Part No.	Type
Normally closed			
	Semi in-line valve with thread G $\frac{1}{8}$	173174	VL-5/3G- $\frac{1}{8}$ -B
	Sub-base valve	173175	VL-5/3G-5,0-B
	Semi in-line valve for manifold PRS-ME	173176	VL-5/3G- $\frac{1}{8}$ -P-B
Normally exhausted			
	Semi in-line valve with thread G $\frac{1}{8}$	173177	VL-5/3E- $\frac{1}{8}$ -B
	Sub-base valve	173178	VL-5/3E-5,0-B
	Semi in-line valve for manifold PRS-ME	173179	VL-5/3E- $\frac{1}{8}$ -P-B
Normally pressurised			
	Semi in-line valve with thread G $\frac{1}{8}$	173180	VL-5/3B- $\frac{1}{8}$ -B
	Sub-base valve	173181	VL-5/3B-5,0-B
	Semi in-line valve for manifold PRS-ME	173182	VL-5/3B- $\frac{1}{8}$ -P-B

Solenoid/pneumatic valves, midi pneumatics

FESTO

Accessories

Individual sub-bases AS, AU

Material:
Die-cast aluminium





Dimensions – Individual sub-bases


Download CAD data → www.festo.com

AS-ME-1/8

AS-VL-1/8



AU-ME-1/8



Ordering data

Brief description		Pneumatic connection		Weight [g]	Part No.	Type
		1, 2, 3, 4, 5	82, 84			
For solenoid valves	Connection at side	G1/8	M5	50	33405	AS-ME-1/8
For pneumatic valves				50	152803	AS-VL-1/8
For valves type ...-1/8-P	Connection underneath			15	32797	AU-ME-1/8

Solenoid/pneumatic valves, midi pneumatics

Accessories


FESTO

Series sub-bases

AW, EP, ZP

Material:


Die-cast aluminium



Dimensions

Download CAD data → www.festo.com

Manifold mounting



Ordering data					
Designation	Brief description	Scope of delivery	Weight [g]	Part No.	Type
Series sub-base	For solenoid valves	1 sub-base, seals and fastening screws	75	33406	AW-ME-1/8
	For pneumatic valves			152801	AW-VL-1/8
Blanking plate for spare positions	–	–	–	31798	PRMEB-5
End plate kit	–	2 end plates, seals and fastening screws	160	33407	EP-ME-1/8
Intermediate plate	With additional P connection	–	95	152592	ZP-ME-1/8-P
	With separate P connection to form pressure zones			152591	ZP-ME-1/8-Z


Solenoid/pneumatic valves, midi pneumatics

FESTO

Accessories


Manifold PRS-ME

Material:
Die-cast aluminium



Dimensions

Download CAD data → www.festo.com



Number of valve positions	L1	L2
2	56	46
3	74	64
4	92	82

Number of valve positions	L1	L2
5	110	100
6	128	118
7	146	136

Number of valve positions	L1	L2
8	164	154
9	182	172
10	200	190

Ordering data – Manifold block

Pneumatic connection	Number of valve positions	Weight [g]	Part No.	Type
1, 3, 5	2, 4	82, 84		
G1/4	G1/8 on valve	M5		
	2	200	33408	PRS-ME-1/8-2
	4	300	33409	PRS-ME-1/8-4
	6	430	33410	PRS-ME-1/8-6
	8	540	33411	PRS-ME-1/8-8
	10	680	33412	PRS-ME-1/8-10

Ordering data – Blanking plate

Brief description	Part No.	Type
Blanking plate for spare positions	31799	PRSB-ME-1/8

-  - Note

For combined assembly of series sub-bases AW-ME-1/8 and AW-VL-1/8, the following assembly sequence must be observed:


1. End plate with air supply
2. Series sub-bases for solenoid valves
3. Series sub-bases for pneumatic valves
4. End plate with flange screw

Solenoid/pneumatic valves, midi pneumatics

Accessories

FESTO


Ordering data			
	Brief description	Part No.	Type
Push-in/threaded fittings QS			
	–	➔	Internet: quick star
Silencers			
	–	➔	u
Manual override tool, detenting			
	For midi valves MEH, MOEH, JMEH	152797	AHB-ME-1/8
		Technical data ➔ Internet: ahb	

Ordering data – Plug sockets, plug sockets with cable, illuminating seal for EB solenoid coils					
	Voltage	Cable length [m]	Switching status display with LED	Part No.	Type
Plug socket without cable					
				Technical data ➔ Internet: mssd	
	–	–	–	151687	MSSD-EB
	–	–	–	539712	MSSD-EB-M12
Plug socket without cable with insulation displacement technology					
				Technical data ➔ Internet: mssd	
	–	–	–	192745	MSSD-EB-S-M14
PVC plug socket with cable					
				Technical data ➔ Internet: kmeb-1	
	24 V DC	2.5	■	151688	KMEB-1-24-2,5-LED
	24 V DC	5	■	151689	KMEB-1-24-5-LED
	24 V DC	10	■	193457	KMEB-1-24-10-LED
	Up to 240 V	2.5	–	151690	KMEB-1-230AC-2,5
	Up to 240 V	5	–	151691	KMEB-1-230AC-5
PUR plug socket with cable					
				Technical data ➔ Internet: kmeb-2	
	24 V DC	2.5	■	174844	KMEB-2-24-2,5-LED
	24 V DC	5	■	174845	KMEB-2-24-5-LED
	Up to 240 V	2.5	–	174846	KMEB-2-230-2,5
	Up to 240 V	5	–	174847	KMEB-2-230-5
Illuminating seal					
				Technical data ➔ Internet: mebl-d	
	12 ... 24 V DC	–	–	151717	MEB-LD-12-24DC
	230 V AC	–	–	151718	MEB-LD-230AC

Solenoid/pneumatic valves, midi pneumatics

Accessories

FESTO

Ordering data – Plug sockets, plug sockets with cable, illuminating seal for E solenoid coils					
	Voltage	Cable length [m]	Switching status display with LED	Part No.	Type
Plug socket without cable				Technical data ➔ Internet: mssd	
	–	–	–	14098	MSSD-E
				539711	MSSD-E-M12
Plug socket with cable				Technical data ➔ Internet: kme	
	24 V DC	2.5	■	30943	KME-1-24DC-2,5-LED
		5	■	30945	KME-1-24DC-5-LED
		10	■	193455	KME-1-24DC-10-LED
Illuminating seal				Technical data ➔ Internet: me-ld	
	24 V DC	–	–	19141	ME-LD-12-24DC

Festo North America



**1 Festo Canada
Headquarters**
Festo Inc.
5300 Explorer Drive
Mississauga, ON
L4W 5G4

2 Montréal
5600, Trans-Canada
Pointe-Claire, QC
H9R 1B6

3 Québec City
2930, rue Watt#117
Québec, QC
G1X 4G3



**4 Festo United States
Headquarters**
Festo Corporation
395 Moreland Road
Hauppauge, NY
11788

5 Appleton
North 922 Tower View Drive, Suite N
Greenville, WI
54942

7 Detroit
1441 West Long Lake Road
Troy, MI
48098

6 Chicago
85 W Algonquin - Suite 340
Arlington Heights, IL
60005

8 Silicon Valley
4935 Southfront Road, Suite F
Livermore, CA
94550

Festo Regional Contact Center

Canadian Customers

Commercial Support:

Tel: 1 877 GO FESTO (1 877 463 3786)

Fax: 1 877 FX FESTO (1 877 393 3786)

Email: festo.canada@ca.festo.com

Technical Support:

Tel: 1 866 GO FESTO (1 866 463 3786)

Fax: 1 877 FX FESTO (1 877 393 3786)

Email: technical.support@ca.festo.com

USA Customers

Commercial Support:

Tel: 1 800 99 FESTO (1 800 993 3786)

Fax: 1 800 96 FESTO (1 800 963 3786)

Email: customer.service@us.festo.com

Technical Support:

Tel: 1 866 GO FESTO (1 866 463 3786)

Fax: 1 800 96 FESTO (1 800 963 3786)

Email: product.support@us.festo.com

Subject to change

Internet: www.festo.com/us